



Grinding-polishing machine for marble, terrazzo, concrete (and similar) floors. Suitable for granite and hard stone as well, only using special diamond abrasives.

- Sturdy and compact structure.
- Three-phase motor driven by frequency inverter thus improving machine output.
- Selection of four different speeds to optimize working of the floor.
- Available with "Prismatic", "Frankfurt" or "Comma" type abrasive holding plate.
- Machine level adjustment by eccentric wheel axis.
- Transport handle and pivoting wheel facilitate machine movements.



Power	4 kW
Voltage	400 V 3-phase
Motor rpm	1400
Abrasive holding plate	320 mm




Plate RPM and peripheral speed	I - 373 rpm - 374 m/min. II - 466 rpm - 468 m/min. III - 559 rpm - 561 m/min. IV - 653 rpm - 656 m/min.
--------------------------------	--

Water tank capacity	31 l
Size	520x1055x1300 mm
Dimensions of palletized carton	540x1100x1200 mm
Net weight without accessories	133 kg
Gross weight	153 kg

ACCESSORIES PROVIDED

Abrasive holding plate
Shock-absorbing spring (outer type)
Shock-absorbing spring (inner type)
Plastic splashguard ring
Squeegee
Set of transportation handles
Set of servicing wrenches

A FRANKFURT
B PRISMATIC
C COMMA

ACHILLI

MACCHINE LAVORAZIONE
MARMILE GRANITI

Achilli s.r.l.

Via Montescudo, 148 - P.O. Box 138 Gros
47900 Rimini (Italia)

Tel. 0541-38.70.66 Fax 0541-38.90.58

achilli@achilli.com

www.achilli.com

